



Jampilen HP525J

Homopolymer

JAMPILen Polypropylene

Description:

Jampilen HP525J is a medium flow homopolymer with bimodal molecular weight distribution and good clarity intended for BOPP films. The product is suitable for metallizable film, both as monolayer and in coextruded structures. It contains a standard processing stabilisation but does not contain any slip, antiblocking agents and is calcium stearate free.

Jampilen HP525J offers good optical properties, easy processing and very stable film profile. Typical applications are BOPP packaging films and Solid Phase Thermoforming sheets.

Jampilen HP525J is suitable for food contact.

Processing Method:

BOPP Film
Thermoforming

Features:

Medium Flow
Good processability
Good transparency and gloss
Homopolymer

Typical Applications:

High quality packaging film for food
Lamination to other films
Metalizable film
Medical packaging
Thermoformed food containers

Approval:

Food

TYPICAL PROPERTIES	VALUE	UNIT	METHOD
Physical			
Melt Flow Rate (230 °C, 2.16kg)	3.0	g/10min	ASTM D1238
Density	0.9	g/cm ³	ASTM D1505
Mechanical			
Flexural Modulus	1400	MPa	ASTM D790
Tensile Strength at Yield	32	MPa	ASTM D638
Tensile Elongation at Yield	9	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	50	J/m	ASTM D256
Thermal			
Vicat softening point (10N)	152	°C	ASTM D1525
H.D.T. (0.46 MPa)	84	°C	ASTM D648
Accelerated oven ageing in air at 150 °C	500	hours	ASTM D3012
Optical			
Haze (20µm)	0.5	%	ASTM D1003

No. 5, North-Falamak St., Eyyanak Blvd., Farahzadi Blvd., Shahrak-e-Qods., Tehran, 1467715171, Iran.
Tel: +9821-84286, Fax: +9821-88563100
Email: info@jppc.ir
www.jppc.ir

This data and information is considered to be correct and offered in good faith as a guide. But we do not warrant or otherwise guarantee the merchantability, fitness for a particular purpose or suitability of this information, products or processes described.